

OVERVIEW - IMCO LINE OF PRODUCTS

CONCRETE SEALERS

CONCRETE REPAIR

FLOOR COATING SYSTEMS

FLOOR RESURFACING

WALLS - CONCRETE

METAL SIDING AND ROOFING

ROOFS

STEEL COATING

BALCONY REPAIRS

TRANSITE PANELS

CONCRETE SEALERS

460 WATER REPELLENT SEALER

- SINGLE COMPONENT
- WATER BASED
- CLEAR, WILL NOT DISCOLOR THE SURFACE
- BEADS WATER
- BREATHABLE
- GASOLINE AND OIL RESISTANT
- VERTICAL, NON-TRAFFIC SURFACES

465 HIGH SOLIDS WR SEALER

- HIGH SOLIDS VERSION OF 460 FOR HORIZONTAL TRAFFIC SURFACES

470 CRYSTAL-LOK

- SINGLE COMPONENT CRYSTALLISING SEALER
- CHEMICALLY REACTS WITH THE CONCRETE
- TRUE PENETRANT SEALER
- CLEAR WATER BASED
- SEALS, HARDENS AND WATER-PROOFS CONCRETE
- CAN BE USED AS A CURING AGENT AND SEALER IN ONE OPERATION.
- INCIDENTAL FOOD CONTACT APPROVED

510S URETHANE

- SINGLE COMPONENT URETHANE
- INTERIOR USE ONLY
- DARKENS SUBSTRATE SLIGHTLY
- GOOD CHEMICAL RESISTANCE
- INCIDENTAL FOOD CONTACT APPROVAL
- HEAVY DUTY TRAFFIC AREAS

530S URETHANE

- SINGLE COMPONENT ALIPHATIC URETHANE
- TOTAL UV RESISTANCE, WILL NOT YELLOW
- WATER CLEAR
- GLOSSY FINISH
- EXCELLENT ABRASION RESISTANCE
- HEAVY DUTY TRAFFIC AREAS

CONCRETE REPAIR

724 JETSET

- 3 COMPONENT POLYMER CONCRETE
- EXCEPTIONAL ABRASION AND CHEMICAL RESISTANCE
- UNSURPASSED ADHESION TO CLEAN CONCRETE
- VERY RAPID CURE - RETURN TO FULL SERVICE IN 1 HOUR
- INTERIOR AND EXTERIOR APPLICATION
- SUB-ZERO TEMPERATURE APPLICATION (-40°C/-40°F)

1260 MG-KRETE

- 2 COMPONENT MAGNESIUM PHOSPHATE CONCRETE
- FAST CURE
- OUTSTANDING ADHESION TO CONCRETE
- SUB-ZERO TEMPERATURE APPLICATION (-10°C/14°F)
- NON-TOXIC/NON-FLAMMABLE
- FINE/REGULAR GRADE
- INCIDENTAL FOOD CONTACT APPROVAL
- SELF PRIMING

FLOOR COATING SYSTEMS

510C URETHANE

- SINGLE COMPONENT MOISTURE CURE
- VERY TOUGH AND DURABLE
- DARKENS ON UV EXPOSURE
- COLOURS OR AMBER CLEAR
- USE 510S AS PRIMER
- BROADCAST SAND FOR NON-SLIP FINISH
- FOOD CONTACT APPROVED
- EXCELLENT TRAFFIC LINE PAINT

530C URETHANE

- SINGLE COMPONENT ALIPHATIC URETHANE
- UV STABLE WILL NOT YELLOW
- HIGH GLOSS
- USE 530S AS PRIMER

735 JETSET

- 2 COMPONENT PROPRIETARY RESIN SYSTEM
- EXTREME CHEMICAL RESISTANCE
- VERY FAST CURE
- USE 710 AS PRIMER
- BROADCAST SAND FOR NON-SLIP FINISH
- FOOD CONTACT APPROVED
- CURES AT SUB-ZERO TEMPERATURES (-40°C/-40°F)

FLOOR RESURFACING

724 JETSET OVERLAY

- TROWEL APPLIED AT 3/16" THICKNESS
- EXTREME HEAVY DUTY APPLICATIONS
- EXCELLENT CHEMICAL AND ABRASION RESISTANCE
- USE 710 PRIMER
- FOR EXTREME CHEMICAL RESISTANCE SEAL WITH 735
- CURES AT SUB-ZERO TEMPERATURES (-40°C/-40°F)
- VERY FAST CURE
- GENERALLY APPLIED BY SKILLED CONTRACTORS
- FOOD CONTACT APPROVAL

1260 MG-KRETE

- TWO COMPONENT MAGNESIUM PHOSPHATE CONCRETE
- OUTSTANDING ADHESION TO CONCRETE
- DEEP POURS TO FEATHEREDGE PLACEMENT
- NON TOXIC
- NON FLAMMABLE
- FAST CURE
- FOOD CONTACT APPROVAL
- CURES AT SUB-ZERO TEMPERATURES (-10°C/14°F)
- FINE AND REGULAR GRADES AVAILABLE

WALLS
CONCRETE BLOCK, POURED CONCRETE AND MASONRY

These walls can be sealed using either 460, 470, 510S or 530S sealers, depending on exposure. (See "SEALERS"). Repair large cracks using 727, 740 or 1260 before coating.

1130 EBM

- WATER-BASED
- ELASTOMERIC MEMBRANE, 300% ELONGATION
- INTERIOR OR EXTERIOR
- WILL SEAL OPEN PORES AND BRIDGE HAIRLINE CRACKS
- ON POROUS SUBSTRATES USE 1110 PRIMER
- WILL COMPLETELY WATER-PROOF

1150 TEXTURECOAT

- WATER BASED
- AGGREGATE FILLED TO HIDE MINOR SURFACE DEFECTS
- FLEXIBLE
- INTERIOR OR EXTERIOR
- SEAL OPEN PORES AND BRIDGE HAIRLINE CRACKS

510C URETHANE

- SINGLE COMPONENT MOISTURE CURE
- VERY TOUGH AND DURABLE
- DARKENS ON UV EXPOSURE
- COLOURS OR AMBER CLEAR
- USE 510S AS PRIMER
- FOOD CONTACT APPROVED

530C URETHANE

- SINGLE COMPONENT URETHANE
- UV STABLE, INTERIOR OR EXTERIOR EXPOSURE
- DECORATIVE WITH HIGH GLOSS
- FLEXIBLE
- ABRASION RESISTANT
- USE 530S AS PRIMER

735 JETSET

- 2 COMPONENT RESIN SYSTEM
- EXTREME CHEMICAL RESISTANCE
- VERY FAST CURE
- USE 710 AS PRIMER
- CURES AT SUB-ZERO TEMPERATURES (-40°C/-40°F)
- FOOD CONTACT APPROVED

METAL SIDING & ROOFING

510A URETHANE

- SINGLE COMPONENT URETHANE
- EXCELLENT ADHESION TO HAND-CLEANED STEEL & AGED PAINTS
- WILL NOT SOFTEN EXISTING SOLVENT SENSITIVE COATINGS
- SELF-PRIME FINISH COAT
- EXCELLENT PRIMER FOR 510C AND 530C

530C URETHANE

- SINGLE COMPONENT URETHANE
- WATER CLEAR OR COLOURED
- HIGH GLOSS
- NON-FADING, NON-CHALKING ON EXTERIOR EXPOSURES
- DURABLE
- CHIP RESISTANT
- USE 510A AS PRIMER

1130 EBM

- ELASTOMERIC 300% ELONGATION
- WATER-BASED
- SELF-PRIMING ON MOST CLEAN SURFACES
- USED WITH FABRIC TO SEAL JOINTS IN SHEETS, PATCH HOLES
- SEALS BOLT HEADS
- UV STABLE
- WILL COMPLETELY WATER-PROOF

1150 TEXTURECOAT

- WATER BASED
- AGGREGATE FILLED TO GIVE TEXTURED FINISH
- FLEXIBLE
- UV STABLE, WILL NOT CHALK

735 JETSET

- EXTREME CHEMICAL RESISTANCE
- TWO COMPONENT PROPRIETARY RESIN SYSTEM
- VERY FAST CURE
- CURES AT SUB-ZERO TEMPERATURES (-40°C/-40°F)
- USE 710 AS PRIMER

ROOFS

1115/1120 **EBM MEMBRANE**

- WATER-BASED, SINGLE-COMPONENT
- ELASTOMERIC 300% ELONGATION
- FLUID APPLIED WATER-PROOFING
- SEAMLESS, SELF-FLASHING SYSTEM, TOTALLY ADHERED
- BREATHING MEMBRANE
- RESTORES, PROTECTS AND WATER-PROOFS INCLINED ROOFS
- BONDS TENACIOUSLY TO VIRTUALLY ANY SUBSTRATE
- UV RESISTANT

USED ON

- EXISTING BUR
- TRANSITE PANELS (ENCAPSULATES ASBESTOS FIBERS)
- STEEL PANELS
- PLYWOOD
- ROLL ROOFING
- CONCRETE
- RIGID FOAM (URETHANE & POLYSTYRENE)
- MOBILE HOMES
- SHINGLES
- AGED MODIFIED BITUMEN
- WITH 1110 PRIMER, WILL WATER-PROOF AND PROTECT NEW MODIFIED BITUMEN ROOFS
- WITH 1113 PRIMER, WILL REPAIR AND RESEAL EXISTING SILICONE-BASED MEMBRANES AND MOST SINGLE-PLY MEMBRANES
- USED WITH FABRIC TO FORM CONTINUOUS, SEAMLESS, TOTALLY ADHERED FLASHINGS
- USE 1150 OVER 1115 SYSTEM FOR TRAFFIC AREAS

STEEL COATINGS
PRIMERS

510A URETHANE ALUMINIUM

- SINGLE COMPONENT URETHANE
- EXCELLENT ADHESION TO HAND-CLEANED STEEL
- FINISH COATS OR USED AS PRIMER FOR SUBSEQUENT TOPCOATS.

710 JET SET PRIMER

- TWO COMPONENT
- VERY RAPID CURE
- REQUIRES SANDBLASTED SURFACE
- SUB-ZERO CURE (-40°C/-40°F)

STEEL COATINGS
FINISH COATS

510C URETHANE

- SINGLE COMPONENT URETHANE
- DARKENS WITH UV EXPOSURE
- VERY TOUGH AND DURABLE
- GOOD CHEMICAL RESISTANCE
- USE 510A AS PRIMER

530C URETHANE

- SINGLE COMPONENT URETHANE
- UV STABLE, INTERIOR OR EXTERIOR EXPOSURE
- HIGH GLOSS
- USE 510A AS PRIMER

735 JET SET SYSTEM

- 2 COMPONENT PROPRIETARY RESIN SYSTEM
- INTERIOR OR EXTERIOR EXPOSURE
- UNSURPASSED CHEMICAL RESISTANCE
- SUB-ZERO TEMPERATURE CURE (-40°C/-40°F)
- USE 710 PRIMER ONLY

APARTMENT BALCONIES

CONCRETE REPAIR

- 1260 MG-KRETE

CONCRETE PROTECTION

- 470 PENETRANT SEALER
- 510S URETHANE SEALER
- 530S URETHANE SEALER
- 530C URETHANE COATING
- 1130 WATER-PROOFING

SEALING TO BUILDING

- 1130 WITH FABRIC

HAND RAILS

- RE-GROUT SUPPORTS - 1260
- RE-PAINT - 510A, 530C

TRANSITE PANELS

1130 EBM

- WATER -BASED
- ELASTOMERIC 300% ELONGATION
- BREATHING MEMBRANE
- KILLS ANY EXISTING BACTERIAL GROWTH ON PANELS
- EFFECTIVELY ENCAPSULATES ASBESTOS PARTICLES
- USE WITH 1110 PRIMER
- USE WITH FABRIC TO SEAL SHEET SEAMS, PATCH HOLES ETC.
- SEALS BOLT HEADS
- COMPLETELY WATERPROOFS

1150 TEXTURECOAT

- WATER BASED
- FLEXIBLE
- APPLIED OVER 1130 SYSTEM TO GIVE DECORATIVE TEXTURE FINISH